



The **RCU2-A10™** supports multiple camera models:

- Atlona HDVS-CAM
- Atlona HDVS-CAM-HDMI
- Lumens VC-TR1
- Minnray UV401A
- Minnray UV570
- Minnray UV540
- VHD V60UL/V61UL/V63UL
- VHD V60CL/V61CL/V63CL

Shown: **Lumens VC-TR1**



RCC-M003-0.3M
USB-A (RCU2-CE™)
to USB-A

PPC-023-0.3M
RJ11 (RCU2-CE™)
to EIAJ-4 Barrel

RCU2-CE™



RCC-M004-1.0M
USB-B (RCU2-HE™)
to USB-A



Laptop

RCU2-HE™



SCTLink™ Cable

Power, Control & Video


The **SCTLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

WPS-12 30VDC
100-240V 47-63Hz
Power Supply



SCTLink™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)



Module Dimensions

RCU2-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

RCU2-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)