

The **RCU2-B10™** supports multiple camera models:


- ClearOne Unite 150 & 200
- Huddlecams HC10X, HC20X & HC30X
- Lumens VC-B30U
- Marshall CV610-U3
- Minnray UV950A
- PTZOptics 12XUSB & 20XUSB
- Sony SRG-120U & SRG-XP1
- Vaddio ConferenceShot FX
- Vaddio ConferenceShot 10
- VDO360 Saber20X & VDO360 CompassX
- VHD V20C, VX110, VX710N, VX710L & VX120
- Yamaha CS-700AV

Shown: **ClearOne Unite 200**



RCC-M004-0.3M
USB-A (RCU2-CE™)
to USB-B

PPC-023-0.3M
RJ11 (RCU2-CE™)
to EIAJ-4 Barrel



RCC-M004-1.0M
USB-B (RCU2-HE™)
to USB-A



Laptop




SCTLink™ Cable
Power, Control & Video

The **SCTLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

WPS-12 30VDC
100-240V 47-63Hz
Power Supply

SCTLink™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)



Module Dimensions

RCU2-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)
RCU2-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)

