



**Poly Studio,
X30 + X50 Cameras**



Laptop

RCC-M004-1.0M
USB-B (RCU2-HE™) to
USB-A (Computer)

RCC-M005-0.3M
USB-A (RCU2-CE™) to USB-C

RCC-C029-0.5M
RJ11 (RCU2-CE™) to Barrel Connector



RCU2-HE™

RemoteCamUSB2™
RCU2-HE™ Head End
www.soundcontrol.net

Control/IR

USB 2.0

SCTLink™

Power

CAT5e/6 STP/UTP • EIA-568A/B

+30VDC

SCTLink™ Cable
Power, Control & Video

The **SCTLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

WPS-12 30VDC
100-240V 47-63Hz
Power Supply



RCU2-CE™


RemoteCamUSB2™
Single Cable Powered Link
RCU2-CE™ Camera End
CAT5e/6 STP/UTP • EIA-568A/B

SCTLink™

SCT Sound Control Technologies
www.soundcontrol.net
©Sound Control Technologies, Inc., 2020

SCTLink™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)



Module Dimensions

RCU2-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

RCU2-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)