



RCU2S-C10™ USB Application Guide

Updated: 3/10/2022



AVer TR311HN, AVer TR313, AVer TR331 & VHD M1000

RCU2S-HE™ Front Panel
Field-Upgradeable microSD Slot

RCC-M004-1.0M
USB-B (RCU2S-HE™) to USB-A




Laptop

3.5mm Audio Cable
Integrator-Supplied

RCC-M005-0.3M
USB-A (RCU2S-CE™) to USB-C

PPC-023-0.3M
RJ11 (RCU2S-CE™) to EIAJ-4 Barrel Connector



RCU2S-HE™

SCTLINK™ Cable

Power, Control & Video

The **SCTLINK™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.


WPS-12 30VDC
100-240V 47-63Hz
Power Supply



RCU2S-CE™

SCTLINK™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)



Module Dimensions

RCU2S-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

RCU2S-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)

