


The **RCU2S-CC8™** supports multiple camera models:

- Panasonic AW-HE20
- Panasonic AW-UE20
- Panasonic AW-HE50
- Panasonic AW-UE50

Shown: **Panasonic AW-UE20**




RCC-M005-0.3M
USB-A (RCU2S-CE™) to USB-C


RCC-C008-0.5M
RJ45 (RCU2S-CE™) Y Cable to 4mm Power Barrel to 8 Pin Mini Din

Module Dimensions
RCU2S-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)
RCU2S-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)

RCU2S-HE™ Front Panel
Field-Upgradeable microSD Slot



RCC-M004-1.0M
USB-B (RCU2S-HE™) to USB-A



SCLink™ Cable
Power, RS232 Control & Video
The **SCLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

WPS-12 30VDC
100-240V 47-63Hz Power Supply

SCLink™ Cable Specs
Integrator-Supplied CAT5e/CAT6 STP/UTP Cable T568A or T568B (100m Max Length)

