



Cisco Room Bar Pro

**RCC-M005-1.0M**  
USB-A (RTK-MINI-RX™) to USB-C

**RCC-H001-1.0M**  
HDMI to HDMI Video Cable  
**RCC-H016-1.0M**  
RJ45 to RJ45 UTP Control Cable

*\*Can be used on Tx or Rx.\**  
WPS-12 30VDC  
100-240V 47-63Hz  
Power Supply



**RTK-MINI-RX™**  
Receiver Module

**SCTLink™ Cable**  
Ethernet/POE | HDMI | USB  
The **SCTLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

**RCC-H016-1.0M**  
RJ45 to RJ45 UTP Control Cable



**Cisco Navigator**  
Ethernet/POE  
*\*Cisco Provided\**



**RTK-MINI-TX™**  
Transmitter Module


**RCC-M006-1.0M**  
USB Micro B (RTK-MINI-TX™) to USB-A



**Laptop**

**RCC-H001-1.0M**  
HDMI to HDMI Video Cable

**SCTLink™ Cable Specs**  
Integrator-Supplied CAT6 STP/UTP Cable  
T568A or T568B (10m-100m min/max Length)



### Module Dimensions

RTK-MINI-TX™: **H:** 1.394" (35mm) **x W:** 7.283" (185mm) **x D:** 4.484" (114mm)  
RTK-MINI-RX™: **H:** 1.394" (35mm) **x W:** 7.283" (185mm) **x D:** 4.484" (114mm)