

RC-SDA™ Distribution Amplifier (2021) Product Specification

Updated: 3/16/2022





FRONT

BACK

The RC-SDA™ Serial Distribution Amplifier opens up a new world of flexibility options when integrating Poly cameras or codecs.

Poly's unique camera output and codec input requirements have traditionally limited integration with other manufacturer's codecs, cameras, video switchers, and soft codecs.

The RC-SDA™ solves these issues by making devices Poly-friendly, allowing integrators to design more customized and complex systems than ever before possible.

KEY FEATURES

- Supports Poly camera stand-alone installations.
- Facilitates integration of Poly codecs with non-Poly cameras.
- · Simple Plug & Play installation, no programming required.
- Integrated 1x2 HDMI Distribution Amplifier
- Integrated RS232 Port to enable camera control via third party control systems.
- · Can be used in conjunction with either our RemoteCam4[™] or RemoteCam7[™] extension kits.

2021 Version Updates

- Translates Poly to VISCA and VICSA to Poly RS232 Protocols.*
- Field-upgradable firmware via microSD Card.
- In high security environments, the microSD Card slot can be disabled.
- 8 position Dip Switch (previously 4) for greater configuration flexibility.

TECHNICAL SPECS

Video Format: HDMI, up to 1920x1080p @60Hz

- · Video Input: HDMI from Camera
- Video Output 1: HDMI to Poly Codec
- Video Output 2: HDMI Secondary Output
- RS232 Connector: 9-Pin D-Sub Male From Camera, IR Passthrough on Pin 9
- RS232 Connector: 9-Pin D-Sub Male To Codec, IR Passthrough on Pin 9
- RS232 3-Pin: Third Party Control System

MODULE & POWER SUPPLY SPECS

RC-SDA™ (2021) Module

- Imperial Dims: H: 1.51" x W: 3.81" x D: 3.52"
- Metric Dims: H: 38mm x W: 96mm x D: 89mm
- Weight: 0.5 lbs / 226g
- Power Consumption: 2.7W

WPS-12™ Power Supply (Included)

- Imperial Dims: H: 1.19" x W: 1.85" x D: 4.65"
- Metric Dims: H: 30mm x W: 47mm x D: 118mm
- Weight: 0.5 lbs / 236g
- Input: 100 to 240VAC, 47-63Hz, 1.45A Max
- Output: 30VDC, 2A Max
- Output Connector: 5.5mm x 2.5mm DC Barrel
- Regulatory Approvals:

UL, CE, FCC, CCC, TÜV, RCM+GEMS, LPS, BIS, PSE, CB, DoE VI, CoC V5 & RoHS2

SUPPORTED DEVICES

www.soundcontrol.net/product/rc-sda

Cameras Poly EagleEyelV, Poly Director II, and non-Poly cameras.

Codecs Poly RPG300, RPG500, RPG700, RPG7500

RACK SHELVES

RC-RKM™ 2RU 12" Deep Rack Shelf

www.soundcontrol.net/product/rc-rkm-rack-shelf

- Designed to mount the RCU2-HE[™], RC4-HE[™], RC5-HE™, RC6-HE™, RC7-HE™, RC8-HE™, RTK-RX™ and RC-SDA™ modules, specific manufacturer codecs, and power supplies.
- · Leaves access to rear of modules for clean and easy cabling, while providing proper ventilation.

RC-RK2™ 1RU 9" Deep Rack Shelf www.soundcontrol.net/product/rc-rk2-rack-shelf

- Designed to mount two of our RCU2-HE™, RC4-HE™, RC5-HE™, and RC-SDA™ modules, and two of our WPS-12[™] power supplies.
- Leaves access to rear of modules for clean and easy cabling.

RC-RK4™ 1RU 14" Deep Rack Shelf www.soundcontrol.net/product/rc-rk4-rack-shelf

- Designed to mount four of our RCU2-HE™, RC4-HE[™], RC5-HE[™], and RC-SDA[™] modules, and four of our WPS-12[™] power supplies.
- · Leaves access to rear of modules for clean and easy cabling.

PRODUCT WARRANTIES

www.soundcontrol.net/support

Included: 3 Year Standard Available: 2 Year Extended Advance Replacement Limited Warranty



Advance Replacement Limited Warranty



SOLUTION FINDER

Not sure where to start? Try our Solution Finder! www.soundcontrol.net/solution-finder



^{*}Requires firmware v5.0 or later.