





RemoteCam5™ Series Product Specification

Updated: 12/2/2024

Sound Control Technologies (SCT) Camera Extension Kits are designed to streamline the installation of digital video PTZ camera systems.

By simplifying complex cabling and extending traditional distance limitations up to 100m, SCT's extension kits provide integrators with cost and time saving solutions.

KEY FEATURES

- Extends power (no factory camera PSU required), PTZ control and video over a CAT5e/CAT6 cable between 10m-100m.
- Specifically supports Ethernet-controlled cameras.
- Ethernet streaming video supported on 10/100 capable devices
- Simple Plug & Play installation, no programming required.
- Allows pass-through of manufacturer firmware updates from codec to camera.
- All hardware-specific camera and codec connection cables included.
- PowerSniffer included for testing SCTLink™ cable conductor continuity.
- Integrator only required to provide CAT5e/CAT6 SCTLink™ Cable.

TECHNICAL SPECS

- Video Format: HDMI, up to 1920x1080p @60Hz with HDCP support.
- Ethernet Connectivity (RC5-CE™): Single 10/100 Port
- Ethernet Connectivity (RC5-HE™): 10/100 Two Port Layer 2 Ethernet Switch

SCTLINK™ CABLE SPECS

SCT recommends CAT6 or better cable for the SCTLink™. The use of a shielded cable, while not required for most platforms, is highly recommended.

Proper termination and testing, along with good cable management, minimizes potential problems.

Wiring Termination Standard

T568A or T568B 10m Minimum - 100m Maximum Length

Power Consumption

A linked kit will consume 7.5W, *plus* the power consumption of the attached camera.

MODULE & POWER SUPPLY SPECS

RC5-CE™ Camera End Module

- Imperial Dims: H: 0.93" x W: 2.5" x D: 3.741"
- Metric Dims: H: 23mm x W: 63mm x D: 95mm
- Weight: 0.3 lbs / 136g

RC5-HE™ Head End Module

- Imperial Dims: H: 1.504" x W: 3.813" x D: 3.617"
- Metric Dims: H: 38mm x W: 96mm x D: 91mm
- Weight: 0.5 lbs / 226g

WPS-12™ Power Supply (Included)

- Imperial Dims: H: 1.19" x W: 1.85" x D: 4.65"
- Metric Dims: H: 30mm x W: 47mm x D: 118mm
- Weight: 0.5 lbs / 236g
- Input: 100 to 240VAC, 47-63Hz, 1.45A Max
- Output: 30VDC, 2A Max
- Output Connector: 5.5mm x 2.5mm DC Barrel
- Regulatory Approvals:

UL, CE, FCC, CCC, TÜV, RCM+GEMS, LPS, BIS, PSE, CB, DoE VI, CoC V5 & RoHS2

SUPPORTED DEVICES

www.soundcontrol.net/products/ camera-extension-kits/remotecam5-platform

Cameras

Or visit our Solution Finder at www.soundcontrol.net/solution-finder

CAMERA-SPECIFIC MOUNTS

RCM™ Series On-Wall Mounts www.soundcontrol.net/products/ camera-mounts/rcm-on-wall-mounts

- · Integrate mounting of the camera and the RC5-CE™ Camera End Module.
- Camera plates are laser cut to match the contour of the camera base.
- Cleanest mounting solution available, using an integrator-supplied US standard 2-Gang Box or Low Voltage Ring.
- · Provides cable concealment and ease of installation.
- An RCW[™] Series variant is also available for masonry or other solid walls where a 2-Gang Box or Low Voltage Ring cannot be used.

RCR™ Series In-Wall Recessed Mounts www.soundcontrol.net/products/ camera-mounts/rcr-recessed-mounts

- · Integrate mounting of the camera and the RC5-CE™ Camera End Module.
- Three-piece all-metal solution with a common back box and bezel.
- Camera plates are laser cut to match the contour of the camera base.
- · Camera plate has depth mounting options to meet specific requirements.
- Designed to meet ADA compliance in most cases (camera dependent).

RCS™ Series Sheetrock Ceiling Mounts www.soundcontrol.net/products/ camera-mounts/rcs-sheetrock-ceiling-mounts

- · Integrate mounting of the camera and the RC5-CE™ Camera End Module.
- Three-piece all-metal solution with a common Backbox.
- Camera specific with a custom cradle or a ¼ 20 bolt to securely hold the base of the camera.

RCT™ Series T-Bar Ceiling Mounts www.soundcontrol.net/products/ camera-mounts/rct-t-bar-ceiling-mounts

· Integrate mounting of the camera and

- the RC5-CF™ Camera End Module.
- Three-piece all-metal solution with a common T-Bar Bracket.
- Camera specific with a custom cradle or a ¼ 20 bolt to securely hold the base of the camera.

RACK SHELVES

RC-RKM™ 2RU 12" Deep Rack Shelf www.soundcontrol.net/product/rc-rkm-rack-shelf

- Designed to mount the RCU2-HE[™], RC4-HE[™], RC5-HE™, RC6-HE™, RC7-HE™, RC8-HE™, RTK-RX™ and RC-SDA™ modules, specific manufacturer codecs, and power supplies.
- · Leaves access to rear of modules for clean and easy cabling, while providing proper ventilation.

RC-RK2™ 1RU 9" Deep Rack Shelf www.soundcontrol.net/product/rc-rk2-rack-shelf

 Designed to mount two of our RCU2-HE™, RC4-HE™, RC5-HE™, and RC-SDA™ modules, and two of our WPS-12[™] power supplies, while leaving access to rear of modules for clean and easy cabling.

RC-RK4™ 1RU 14" Deep Rack Shelf www.soundcontrol.net/product/rc-rk4-rack-shelf

 Designed to mount four of our RCU2-HE™, RC4-HE™, RC5-HE™, and RC-SDA™ modules, and four of our WPS-12[™] power supplies, while leaving access to rear of modules for clean and easy cabling.

PRODUCT WARRANTIES

www.soundcontrol.net/support

Included: 3 Year Standard **Available:** 2 Year Extended Advance Replacement Limited Warranty





Advance Replacement Limited Warranty



